

Electric Chain Hoist Single Phase CM Lodestar

Product information

The Lodestar features quieter operation, an environment friendly design, easier access to key components, higher duty cycles, less maintenance, and enhanced safety features.

Features:

- · Cast aluminium, lightweight housing covered with acid resistant powder coated paint
- IP 66 enclosure rating
- · Motor thermal protection across all models
- The 5 Pocket Lift Wheel improves chain life through better chain and lift wheel engagement, smoother lifting and reduced vibration
- Overload protector
- · Adjustable screw limit switch that automatically stops the hook at any predetermined point when either lifting or lowering
- Fabric chain container and rigid hook suspension as standard
- Primary and secondary transformer fusing
- EN grade zinc plated load chain (optional black phosphate or stainless steel chain)
- Metal and stainless steel chain containers (optional)
- Swivel top hook suspension (optional)
- Double DC brake (optional)
- Heavy-duty DC brake is designed for a long service life
- Clutch is located outside the load path preventing slipping of the load in an overload condition when the brake is not powered
- Lifetime grease-lubricated Gear Box means no oil change is required

WLL ton	Lifting speed m/min	Number of falls	A mm	B mm	C mm	D mm	F mm	H mm	l mm	J mm	M mm	P mm	Weight kg	Delivery time
0.25	8.1	1	429	201	18	298	225	25	113	113	30	168	28	2
0.5	4.1	1	429	201	18	298	225	25	113	113	30	168	28	2
1	4.1	1	496	193	21	255	330	28	178	143	32	208	51	2
2	2	2	613	194	29	253	329	38	179	142	33	208	59	2
3	1.4	3	613	194	29	253	329	38	179	142	33	208	72	2

Blueprint

