

Fixed Jaw Super Clamp WH BC

Product information




The WH BC fixed jaw super clamp is fitted with a 'gusset' in both jaws maximising contact between the beam and clamp thus increasing the grip. A shackle is fitted to the bottom allowing an easy connection of the hoist to be attached. This fixed jaw super clamp can be used to an angle of 45° to the vertical. When the angle is moved away from the vertical the working load limit of the beam clamp needs to be reduced. Please refer to the table opposite – reduction in working load limits when side loads are applied.

... [Read more](#)

Fixed Jaw Super Clamp WH BC

Blueprint



Technical data

| Part code | WLL ton | Beam width mm | A mm | B mm | D mm | E max mm mm | E min mm mm | G, mm | K max mm | K minmm mm | H, mm | Weight kg |
|-----------------|---------|---------------|------|------|-------|-------------|-------------|-------|----------|------------|-------|-----------|
| 502300201900790 | 2 | 76-190 | 130 | 3 | 90 | 254 | 133 | 275 | 263 | 223 | 20 | 4 |
| 502300321900790 | 3.2 | 76-190 | 130 | 12 | 102 | 275 | 166 | 275 | 289 | 251 | 20 | 8 |
| 502300323500790 | 3.2 | 127-350 | 130 | 12 | 102 | 438 | 228 | 560 | 375 | 294 | 20 | 11.5 |
| 502300402540790 | 4 | 150-254 | 130 | 10 | 112 | 371 | 185 | 410 | 369 | 308 | 25 | 11 |
| 502300501900790 | 5 | 76-190 | 130 | 12 | 116 | 306 | 191 | 295 | 338 | 300 | 25 | 10 |
| 502300503050790 | 5 | 150-305 | 130 | 12 | 116 | 422 | 264 | 410 | 413 | 360 | 25 | 15 |
| 502300604570790 | 6 | 203-457 | 140 | 12 | 116 | 608 | 267 | 560 | 511 | 402 | 25 | 18.8 |
| 502301004570790 | 10 | 203-457 | 140 | 20 | 118 | 608 | 267 | 560 | 530 | 421 | 32 | 28 |
| 502301504570790 | 15 | 203-457 | 170 | 20 | 116.5 | 648 | 400 | 660 | 684 | 608 | 40 | 49.5 |
| 502301506100790 | 15 | 406-610 | 170 | 20 | 116.5 | 800 | 600 | 810 | 812 | 706 | 40 | 58.5 |