

Combi Use Skip

Product information



Designed to simplify the holding, movement and disposal of material in confined areas with the unique '4 way entry' base. The skip is supplied as manual operation as standard, but automatic tipping at high level can be achieved by ordering the conversion kit allowing the forklift / tele handler driver to empty the skip without leaving the safety of his seat.

Standard Features

- Low loading height
- Reinforced leading edge and body sides
- 4 way fork pocket entry
- Secondary Locking Mechanism to prevent accidental discharge
- Fully seam welded for retention of fluids
- Manual handle override
- Maximum fork section 150 x 50 mm at 675 mm centres
- Zinc plated heel pins for safe attachment to truck
- Painted bright orange for safety

Optional Features

- Conversion kit for automatic operation
- 125mm diameter nylon castors
- Colour finish for waste separation or department

... [Read more](#)

Combi Use Skip

Technical data

Part code	WLL ton	Height mm	Width mm	Weight kg
6225ICUS0	0.7	690*	1,030	166
6225ICUS05mm	0.7	690*	1,030	-
6225ICUS1	0.9	830*	1,060	222
6225ICUS15mm	0.9	830*	1,060	-
6225ICUS2	1.2	830*	1,300	229
6225ICUS25mm	1.2	830*	1,300	-
6225ICUS3	1.6	830*	1,560	251
6225ICUS35mm	1.6	830*	1,560	-
6225ICUS4	2.2	955*	1,560	335
6225ICUS45mm	2.2	955*	1,560	-