

Combi Use Skip



Product information

Designed to simplify the holding, movement and disposal of material in confined areas with the unique '4 way entry' base. The skip is supplied as manual operation as standard, but automatic tipping at high level can be achieved by ordering the conversion kit allowing the forklift / tele handler driver to empty the skip without leaving the safety of his seat.

Standard Features

- Low loading height
- Reinforced leading edge and body sides
- 4 way fork pocket entry
- Secondary Locking Mechanism to prevent accidental discharge
- Fully seam welded for retention of fluids
- Manual handle override
- Maximum fork section 150 x 50 mm at 675 mm centres
- Zinc plated heel pins for safe attachment to truck
- Painted bright orange for safety

Optional Features

- Conversion kit for automatic operation
- 125mm diameter nylon castors
- Colour finish for waste separation or department

Part code	WLL ton	Height mm	Width mm	Weight kg	Delivery time
6225ICUS0	0.7	690*	1,030	166	2
6225ICUS05mm	0.7	690*	1,030	-	2
6225ICUS1	0.9	830*	1,060	222	2
6225ICUS15mm	0.9	830*	1,060	-	2
6225ICUS2	1.2	830*	1,300	229	2
6225ICUS25mm	1.2	830*	1,300	-	2
6225ICUS3	1.6	830*	1,560	251	2
6225ICUS35mm	1.6	830*	1,560	-	2
6225ICUS4	2.2	955*	1,560	335	2
6225ICUS45mm	2.2	955*	1,560	-	2