

Fall Protection Anchorage Point SS. PE.SEB



Product information

The Fall Protection Anchorage Point is fitted with an automatic position recovery system for optimum orientation in the direction of the sling.

Features:

- 360° rotation.
- Control anti-crack on 100% of product.

Material: Stainless Steel AISI 316 L

Marking: According to standard

Temperature range: -20°C up to + 200°C

Standard: EN 795

| Part code | Max. number of persons | Thread | Torque Nm | A mm | B mm | C mm | D mm | L1 mm | S mm | Weight kg | Delivery time |
|----------------|------------------------|--------------|-----------|------|------|------|------|-------|------|-----------|---------------|
| 8415SSPESEBM12 | 1 | M 12 (x1.75) | 15 | 38 | 45 | 90 | 80 | 21 | 8 | 0.8 | 2 |
| 8415SSPESEBM16 | 1 | M 16 (x2) | 50 | 38 | 45 | 90 | 80 | 27 | 8 | 0.82 | 2 |
| 8415SSPESEBM20 | 1 | M 20 (x2.5) | 100 | 38 | 45 | 90 | 80 | 30 | 8 | 0.84 | 2 |
| 8415SSPESEBM24 | 1 | M 24 (x3) | 150 | 38 | 45 | 90 | 80 | 36 | 8 | 0.9 | 2 |

Blueprint

