Gantry crane, Porta Gantry Rapide 250-1000 kg

Product information



Goods WLL: Up to 1000kg
Personnel WLL: Up to 500kg
3 Person fall arrest: EN795:1997 certified – as part of an EN363 compliant system.
ATEX: Suitable for use in atex zone 2 explosive atmospheres
Lightweight & portable
Easy use:
- Adaptable, multi-purpose trolleys - goods and personnel rated
- Load bearing, lockable castors for easy positioning (acop advises no gantry movement under load except where a competent person has undertaken a suitable risk assessment & method statement and has deemed appropriate)
Configurations: Range of beam lengths up to 4m and configurations available


Availability: 14 Days

... *Read more*

© November 2026 - All Rights Reserved

Gantry crane, Porta Gantry Rapide 250-1000 kg

Blueprint



Technical data

Part code	WLL ton	Max. number of persons	Standard Beam Length mm	Max user weight kg	Weight kg
6015PGRT20	0.25	1	2,000	125	45
6015PGRS40	0.25	1	4,000	125	46
6015PGRT23	0.25	1	2,300	125	46
6015PGRT40	0.25	1	4,000	125	51
6015PGRS23	0.4	2	2,300	200	41
6015PGRM20	0.4	2	2,000	200	41
6015PGRM23	0.4	2	2,300	200	42
6015PGRM40	0.4	2	4,000	200	47
6015PGRS20	0.5	3	2,000	250	40

© November 2026 - All Rights Reserved

Gantry crane, Porta Gantry Rapide 250-1000 kg

Dimensions (mm)														
Model	A Beam Length	B	C Min	C Max	D Min	D Max	E Min	E Max	F Min	F Max	G	H Min	H Max	J
PGRS20	2000	2076	1100	1500	1738	1938	1914	2114	2064	2264	1158	1850	2050	2190
PGRS23	2300	2376	1200	1800										2376
PGRS40	4000	4076	2700	3500										4076
PGRM20	2000	2076	1100	1500	1642	2042	1818	2218	1968	2368	1215	1755	2155	2190
PGRM23	2300	2376	1200	1800										2376
PGRM40	4000	4076	2700	3500										4076
PGRT20	2000	2076	1100	1500	1916	2816	2092	2992	2242	3142	1586	2028	2928	2631
PGRT23	2300	2376	1200	1800										2631
PGRT40	4000	4076	2700	3500										

© November 2026 - All Rights Reserved