



Screw Pin Anchor Shackle Crosby G-209

Product information

Screw pin anchor shackles meet the performance requirements of Federal Specification RR-C-271G Type IVA, Grade A, Class 2, except for those provisions required of the contractor.

Proof load: 2 x WLL.

Material: Carbon steel with headbolt in alloy steel.

Marking: According to standard, CE-marked

Temperature range: -40° C (-40° F) up to 204° C (400° F)

Finish: Hot dip galvanized.

Standard: EN 13889

Safety factor: 6:1

Grade: 6

Part code	WLL ton	Size inch	A mm	B mm	C mm	D mm	E mm	F mm	G mm	H mm	L mm	M mm	P mm	A Tolerance +/-	C Tolerance +/-	Weight kg	Delivery time
420100030190	0.33	3/16	10	6	22	5	15	14	25	37	4	29	5	1.5	1.5	0.03	2
420100050190	0.5	1/4	12	8	29	6	20	16	32	47	5	36	6	1.5	1.5	0.05	2
420100750190	0.75	5/16	14	10	31	8	21	19	37	53	6	43	8	1.5	3.3	0.09	2
420100100190	1	3/8	17	11	37	10	26	23	46	64	6	52	10	1.5	3.3	0.14	2
420100150190	1.5	7/16	19	13	43	11	30	27	52	74	8	60	11	1.5	3.3	0.17	2
420100200190	2	1/2	21	16	48	13	33	30	59	83	10	68	13	1.5	3.3	0.33	2
420100330190	3.25	5/8	27	19	60	16	43	38	74	106	11	85	18	1.5	6.4	0.62	2
420100480190	4.75	3/4	32	22	71	19	51	46	89	126	13	101	21	1.5	6.4	1.07	2
420100650190	6.5	7/8	37	25	84	22	58	53	103	148	13	114	25	1.5	6.4	1.64	2
420100850190	8.5	1	43	30	96	25	68	60	119	167	14	130	27	1.5	6.4	2.28	2
420100950190	9.5	1 1/8	46	32	108	30	74	68	131	190	16	152	32	1.5	6.4	3.36	2
420101200190	12	1 1/4	52	36	119	33	83	76	146	210	18	165	35	1.5	6.4	4.31	2
420101350190	13.5	1 3/8	57	40	133	36	92	84	162	233	19	176	38	3.3	6.4	6.14	2
420101700190	17	1 1/2	60	42	146	39	99	92	176	254	21	189	41	3.3	6.4	7.8	2
420102500190	25	1 3/4	73	52	178	47	127	106	224	313	25	233	57	3.3	6.4	14.02	2
420103500190	35	2	83	58	197	53	146	122	258	347	29	263	61	3.3	6.4	20.4	2
420105500190	55	2 1/2	105	71	267	69	184	148	324	455	35	335	80	6.4	6.4	38.9	2

Blueprint

