



Closed Spelter Socket Green Pin® G-6411

Product information

The Green Pin® Closed Spelter Socket is made from high tensile steel. Its long-term durability is assured due to galvanization. The Green Pin® Closed Spelter Socket is available for a diameter wire rope of 6-7 up to 120-130 mm and can be used in combination with the Socket Lock Socketing Resin.

Certification on request: 2.1, 2.2, 3.1

Material: High Tensile Steel

Marking: CE-marked

Temperature range: -20°C up to +200°C

Finish: Hot Dipped Galvanized

Part code	Rope Ø range mm	MBL ton	Finish	a mm	b mm mm	c mm	dmm mm	e mm mm	f mm mm	g mm mm	Weight kg	Delivery time
122100700372	6-7	8	Galvanized	101	37	22	40	11	13	9	0.26	2
122101000372	8-10	12	Galvanized	119	43	25	48	14	17.5	12	0.5	2
122101300372	11-13	20	Galvanized	140	52	30	58	18	23.5	15	0.72	2
122101600372	14-16	25	Galvanized	162	68	37	66	21	26	17.5	1.47	2

122101900372	18-19	45	Galvanized	194	76	42	78	27	32	21.5	2.24	2
122102200372	20-22	70	Galvanized	224	92	47	90	33	38	24	4.2	2
122102600372	23-26	85	Galvanized	253	104	57	103	36	44	28	6.03	2
122103000372	27-30	105	Galvanized	282	114	63	116	39	51	32	7.85	2
122103600372	31-36	136	Galvanized	312	127	70	130	43	57	38	10.8	2
122103900372	37-39	150	Galvanized	358	136	79	155	51	63	41	13.6	2
122104200372	40-42	170	Galvanized	390	146	83	171	54	70	44	17	2
122104800372	43-48	225	Galvanized	443	171	93	198	55	76	51	26	2
122105400372	49-54	280	Galvanized	502	193	100	224	62	82	57	37.5	2
122106000372	55-60	360	Galvanized	548	216	112	247	73	92	63	54.5	2
122106800372	61-68	425	Galvanized	597	241	140	270	79	102	73	69.5	2
122107500372	69-75	460	Galvanized	644	273	159	286	79	124	79	100	2
122108000372	76-80	560	Galvanized	686	292	171	298	83	133	86	121	2
122108600372	81-86	625	Galvanized	743	311	184	311	102	146	92	156	2
122109300372	87-93	720	Galvanized	788	330	197	330	102	159	99	181	2
122110200372	94-102	875	Galvanized	845	362	216	356	108	178	108	210	2
122111500372	108-115	1,200	Galvanized	1,000	405	235	425	125	190	125	334	2
122113000372	120-130	1,300	Galvanized	1,150	450	260	525	125	200	143	500	2

Blueprint

