

## Wire Rope Clip with casted Bridge POWERTEX PCTA

**Product information** 





The Powertex Wire Rope Clip with Casted Bridge PCTA is suitable for suspending static loads and single-use lifting operations. Available in sizes for wire rope from 5 mm to 40 mm, this wire rope clip is designed and tested in accordance with the EN 13411-5(type A) standard, ensuring compliance and reliability in every use.

## Product benefits

- <u>Safety compliance:</u> these wire rope clips comply with EN 13411-5(Type A) standards, meeting stringent safety and quality requirements.
- High load capacity: when correctly mounted, the assembly can withstand up to 80% of the rope's minimum breaking load (MBL), providing robust and reliable performance.
- Compatibility: designed for use with six-stranded wire ropes in 6x19 (M) and 6x36 classes and ordinary lay wire rope in 8x19 class up to 1960 N/mm², with fibre core and steel core.
- Durable finish: Electrogalvanized (Chrome 6 Free)
- Full traceability: every Wire Rope Clip is marked with Powertex or PX branding, Max Rope Size (mm), and a traceability code, ensuring traceability to the production lot and raw materials.

Material: Carbon steel

Marking: Powertex (PX), Max rope size in mm, Batch no/traceability code

Finish: Electrogalvanized

**Warning:** To be used for suspending static loads and single-use lifting operations. Not suitable for use with compacted, hammered, or plastic-covered steel wire ropes. Additionally, these clips should not be used with spiral strand ropes.

## Blueprint

