

## Double Swivel Ring Codipro OS DSR UP UNC



### Product information

**Standard metric and UNC threads available**

**M 5 to M 42**

WLL 0.07 ton to 9.00 ton

**UNC 1/4" to UNC 1" 1/4**

WLL 330 lbs to 13,500 lbs

- Swing under load 360° rotation - 180° swing.
- Complies with Machinery Directive 2006/42/CE.
- Produced in accordance with the EN 1677-1 standard.
- Safety factor 4:1 and 5:1.

**Marking:** CE-marked, Individual marking

**Safety factor:** 5:1

| Part code       | WLL ton | Thread Inch  | Torque Nm | A, | B, | C, | D, | E, | F, | G,  | H,  | L1 mm | S1 mm | S2 mm | Weight kg | Delivery time |
|-----------------|---------|--------------|-----------|----|----|----|----|----|----|-----|-----|-------|-------|-------|-----------|---------------|
| 4215OSDSRU050UP | 0.6     | UNC 3/8"-16  | 8         | 32 | 30 | 30 | 38 | 27 | 14 | 53  | 9.5 | 17    | 8     | 16    | 0.3       | 2             |
| 4215OSDSRU038UP | 1.1     | UNC 1/2"-13  | 12        | 32 | 30 | 30 | 38 | 27 | 14 | 53  | 9.5 | 21    | 8     | 16    | 0.3       | 2             |
| 4215OSDSRU058UP | 1.8     | UNC 5/8"-11  | 40        | 45 | 40 | 45 | 53 | 38 | 17 | 76  | 13  | 27    | 8     | 20    | 0.9       | 2             |
| 4215OSDSRU075UP | 2.4     | UNC 3/4"-10  | 80        | 45 | 40 | 45 | 53 | 38 | 17 | 76  | 13  | 30    | 8     | 20    | 0.9       | 2             |
| 4215OSDSRU100UP | 5       | UNC 1"-8     | 125       | 62 | 55 | 60 | 83 | 55 | 25 | 115 | 19  | 36    | 14    | 24    | 2.6       | 2             |
| 4215OSDSRU125UP | 6.1     | UNC 1" 1/4-7 | 200       | 62 | 55 | 60 | 83 | 55 | 25 | 115 | 19  | 45    | 14    | 24    | 2.7       | 2             |

## Technical data

# Blueprint

