



## Weld-on Swivel Hoist Ring Codipro WE DSS

### Product information

- Weld-on swivel hoist ring.
- 360° rotation.
- Swivelling under load.
- 180° articulation.
- Control anti-crack on 100% of the product.
- Fatigue test.

**Marking:** According to standard, CE-marked

**Temperature range:** -20°C up to + 200°C

**Standard:** EN 1677-1

**Safety factor:** 5:1

| Part code   | WLL ton | A mm | a mm | B mm | C mm | D mm | E mm | F mm | G mm | Weight kg | Delivery time |
|-------------|---------|------|------|------|------|------|------|------|------|-----------|---------------|
| 4215WEDSS10 | 10      | 74   | 7    | 44   | 70   | 104  | 73   | 149  | 33   | 5.5       | 2             |

Technical data

5:1

max. load in t

| METRIC THREADS  |       |       |       |       |          |           |            |          |           |            |
|-----------------|-------|-------|-------|-------|----------|-----------|------------|----------|-----------|------------|
|                 |       |       |       |       |          |           |            |          |           |            |
| Number of rings | 1     | 2     | 1     | 2     | 2        |           |            | 3 → 4    |           |            |
| Lifting angle β | 0°    | 0°    | 0°    | 0°    | 0° → 45° | 45° → 60° | Asymmetric | 0° → 45° | 45° → 60° | Asymmetric |
| Loading angle α | 0°    | 0°    | 90°   | 90°   | 0° → 45° | 45° → 60° |            | 0° → 45° | 45° → 60° |            |
| WE.DSR 2        | 2,00  | 4,00  | 2,00  | 4,00  | 2,80     | 2,00      | 2,00       | 4,20     | 3,00      | 2,00       |
| WE.DSR 5        | 5,00  | 10,00 | 5,00  | 10,00 | 7,00     | 5,00      | 5,00       | 10,50    | 7,50      | 5,00       |
| WE.DSS 10       | 10,00 | 20,00 | 10,00 | 20,00 | 14,00    | 10,00     | 10,00      | 21,00    | 15,00     | 10,00      |

Blueprint

