Aluminum Wire Rope Hoist Powertex PAPH-S1

Product information



Powertex Aluminum wire rope hoist PAPH-S1 is a compact and lightweight hoist that can be used for lifting, pulling and tightening offering very long lifting heights. It works with a steel wire rope running through the jaws of the hoist with a pulling speed of app. 3 m/min. The double sets of jaws open in turns so that the wire rope will always stay tight during the lifting/lowering operation.

20 m coiled steel wire rope with latch hook is included.

Features:

- Safe – Each hoist is dynamic proof load tested 1,25 x WLL before leaving the factory.
- Compact, lightweight construction with aluminum covers.
- Durable construction with powder coated finish and plated frame components.
- Equipped with replaceable shear safety pin that prevents overloading (5 spare pins included in the carrying handle/pulling handle).
- Equipped with rubber protection at the top opening preventing dirt from entering the hoist.
- Carrying handle for easy transportation and handling.
- 20 m coiled steel wire rope with latch hook is included and other lengths can be offered.
- Hooks are designed to open at overload instead of breaking.
- Hooks fitted with heavy duty steel safety latches.
- RFID equipped (chip) for easy service and inspection.
- QR code for on-site access to Multilanguage user manual.
- Test certificate and Declaration of Conformitv enclosed with each h ... *Read more*

Material: Durable aluminium/steel construction, Rubber handle
Marking: According to standard, CE-mark, Powertex, Model, WLL, Wire rope type, Serial number, User manual/QR code.
Temperature range: -10°C up to +50°C
Finish: White powder coated body, plated steel parts and galvanized wire rope / hook.
Standard: EN 13157, EN 13414-1
Note: Only original rope can be used with the hoist!

Safety factor: 4:1

© November 2026 - All Rights Reserved

Aluminum Wire Rope Hoist Powertex PAPH-S1

Blueprint



Technical data

Part code	WLL ton	Lifting height m	Model	Rope Ø mm	Hand force max. kg	A mm	B mm	C mm	D mm	E mm	L1 mm	L2 mm	Weight kg
9850POWPAPHS1008020	0.8	20	Spare Rope	8.3	-	426	235	168	60	64	-	800	6.1
501100082000180	0.8	20	PAPH-S1/800	8.3	34.77	426	235	168	60	64	-	800	6.5
9850POWPAPHS1008050	0.8	50	Spare Rope	8.3	-	426	235	168	60	64	-	800	15.25
9850POWPAPHS10080100	0.8	100	Spare Rope	8.3	-	426	235	168	60	64	-	800	30.5
9850POWPAPHS1016020	1.6	20	Spare Rope	11	-	545	284	190	72	97	692	1,200	11.5
501100162000180	1.6	20	PAPH-S1/1600	11	40.79	545	284	190	72	97	692	1,200	12.5
9850POWPAPHS1016050	1.6	50	Spare Rope	11	-	545	284	190	72	97	692	1,200	28.75
9850POWPAPHS10160100	1.6	100	Spare Rope	11	-	545	284	190	72	97	692	1,200	57.5
9850POWPAPHS1032020	3.2	20	Spare Rope	16	-	660	325	230	91	116	692	1,200	23
501100322000180	3.2	20	PAPH-S1/3200	16	44.66	660	325	230	91	116	692	1,200	23.5
9850POWPAPHS1032050	3.2	50	Spare Rope	16	-	660	325	230	91	116	692	1,200	57.5
9850POWPAPHS10320100	3.2	100	Spare Rope	16	-	660	325	230	91	116	692	1,200	115
9850POWPAPHS1054020	5.4	20	Spare Rope	20	-	930	390	300	110	150	692	1,200	36.5
501100542000180	5.4	20	PAPH-S1/5400	20	86.55	930	390	300	110	150	692	1,200	56
9850POWPAPHS1054050	5.4	50	Spare Rope	20	-	930	390	300	110	150	692	1,200	91.25
9850POWPAPHS10540100	5.4	100	Spare Rope	20	-	930	390	300	110	150	692	1,200	182.5

© November 2026 - All Rights Reserved