

Chain sling 2-leg with latch hook, grade 8

Product information



2-legs chain sling assembly equipped with latch hooks and grab hooks. Alternative ends are also available, e.g. foundry hooks, shackles etc. Slings are equipped with a load plate.

... [Read more](#)

Material: Steel

Marking: According to standard, CE-marked

Temperature range: -40 °C up to +200°C

Finish: Painted, black / yellow

Standard: EN 818-4

Warning: Not to be heat-treated

Safety factor: 4:1

Grade: 8

Chain sling 2-leg with latch hook, grade 8

Technical data

| Part code | Chain diameter mm | WLL ton | EWL m | Weight kg |
|-----------------|----------------------|------------|----------|--------------|
| 230800600100110 | 6 | 1.6 | 1 | 6.61 |
| 230800600200110 | 6 | 1.6 | 2 | 9.44 |
| 230800600300110 | 6 | 1.6 | 3 | 12.27 |
| 230800600400110 | 6 | 1.6 | 4 | 15.1 |
| 230800600500110 | 6 | 1.6 | 5 | 17.93 |
| 230800600600110 | 6 | 1.6 | 6 | 20.76 |
| 230800600700110 | 6 | 1.6 | 7 | 23.59 |
| 230800600800110 | 6 | 1.6 | 8 | 26.42 |
| 230800800100110 | 8 | 2.8 | 1 | 6.61 |
| 230800800200110 | 8 | 2.8 | 2 | 9.44 |
| 230800800300110 | 8 | 2.8 | 3 | 12.27 |
| 230800800400110 | 8 | 2.8 | 4 | 15.1 |
| 230800800500110 | 8 | 2.8 | 5 | 17.93 |
| 230800800600110 | 8 | 2.8 | 6 | 20.76 |
| 230800800700110 | 8 | 2.8 | 7 | 23.59 |
| 230800800800110 | 8 | 2.8 | 8 | 26.42 |
| 230801000100110 | 10 | 4.25 | 1 | 10.49 |
| 230801000200110 | 10 | 4.25 | 2 | 14.92 |
| 230801000300110 | 10 | 4.25 | 3 | 19.35 |
| 230801000400110 | 10 | 4.25 | 4 | 23.78 |
| 230801000500110 | 10 | 4.25 | 5 | 28.21 |
| 230801000600110 | 10 | 4.25 | 6 | 32.64 |
| 230801000700110 | 10 | 4.25 | 7 | 37.07 |
| 230801000800110 | 10 | 4.25 | 8 | 41.5 |
| 230801300100110 | 13 | 7.5 | 1 | 18.62 |
| 230801300200110 | 13 | 7.5 | 2 | 26.12 |
| 230801300300110 | 13 | 7.5 | 3 | 33.62 |
| 230801300400110 | 13 | 7.5 | 4 | 41.12 |
| 230801300500110 | 13 | 7.5 | 5 | 48.62 |
| 230801300600110 | 13 | 7.5 | 6 | 56.12 |
| 230801300700110 | 13 | 7.5 | 7 | 63.62 |

Chain sling 2-leg with latch hook, grade 8

Technical data

| Part code | Chain diameter mm | WLL ton | EWL m | Weight kg |
|-----------------|----------------------|------------|----------|--------------|
| 230801300800110 | 13 | 7.5 | 8 | 71.12 |
| 230801600200110 | 16 | 11.2 | 2 | 42.26 |
| 230801600300110 | 16 | 11.2 | 3 | 53.4 |
| 230801600400110 | 16 | 11.2 | 4 | 64.54 |
| 230801600500110 | 16 | 11.2 | 5 | 75.68 |
| 230801600600110 | 16 | 11.2 | 6 | 86.82 |
| 230801600700110 | 16 | 11.2 | 7 | 97.96 |
| 230801600800110 | 16 | 11.2 | 8 | 109.1 |
| 230802000200110 | 20 | 17 | 2 | 70.1 |
| 230802000300110 | 20 | 17 | 3 | 88.3 |
| 230802000400110 | 20 | 17 | 4 | 106.5 |
| 230802000500110 | 20 | 17 | 5 | 124.7 |
| 230802000600110 | 20 | 17 | 6 | 142.9 |
| 230802000700110 | 20 | 17 | 7 | 161.1 |
| 230802000800110 | 20 | 17 | 8 | 179.3 |
| 230802200200110 | 22 | 21.2 | 2 | 105.7 |
| 230802200300110 | 22 | 21.2 | 3 | 127.7 |
| 230802200400110 | 22 | 21.2 | 4 | 149.7 |
| 230802200500110 | 22 | 21.2 | 5 | 171.7 |
| 230802200600110 | 22 | 21.2 | 6 | 193.7 |
| 230802200700110 | 22 | 21.2 | 7 | 215.7 |
| 230802200800110 | 22 | 21.2 | 8 | 237.7 |
| 230802600200110 | 26 | 30 | 2 | 141.4 |
| 230802600300110 | 26 | 30 | 3 | 172 |
| 230802600400110 | 26 | 30 | 4 | 202.6 |
| 230802600500110 | 26 | 30 | 5 | 233.2 |
| 230802600600110 | 26 | 30 | 6 | 263.8 |
| 230802600700110 | 26 | 30 | 7 | 294.4 |
| 230802600800110 | 26 | 30 | 8 | 325 |