

Chain sling 1-leg with safety hook, grade 10



Product information

1-Leg chain sling assembly equipped with safety hook and grab hook. Alternative ends are also available, e.g. foundry hooks, shackles etc. Slings are equipped with a load plate.

Material: Steel

Marking: CE-marked

Temperature range: -40 °C up to +200°C

Finish: Painted

Warning: Not to be heat-treated

Safety factor: 4:1

Grade: 10

Part code	Chain diameter mm	WLL ton	EWL m	Weight kg	Delivery time
240500600100210	6	1.4	1	3.28	2
240500600200210	6	1.4	2	4.78	2
240500600300210	6	1.4	3	6.28	2
240500600400210	6	1.4	4	7.78	2

240500600500210	6	1.4	5	9.28	2
240500600600210	6	1.4	6	10.78	2
240500600700210	6	1.4	7	12.28	2
240500600800210	6	1.4	8	13.78	2
240500800100210	8	2.5	1	3.28	2
240500800200210	8	2.5	2	4.78	2
240500800300210	8	2.5	3	6.28	2
240500800400210	8	2.5	4	7.78	2
240500800500210	8	2.5	5	9.28	2
240500800600210	8	2.5	6	10.78	2
240500800700210	8	2.5	7	12.28	2
240500800800210	8	2.5	8	13.78	2
240501000100210	10	4	1	5.53	2
240501000200210	10	4	2	7.83	2
240501000300210	10	4	3	10.13	2
240501000400210	10	4	4	12.43	2
240501000500210	10	4	5	14.73	2
240501000600210	10	4	6	17.03	2
240501000700210	10	4	7	19.33	2
240501000800210	10	4	8	21.63	2
240501300100210	13	6.7	1	10.65	2
240501300200210	13	6.7	2	14.55	2
240501300300210	13	6.7	3	18.45	2

240501300400210	13	6.7	4	22.35	2
240501300500210	13	6.7	5	26.25	2
240501300600210	13	6.7	6	30.15	2
240501300700210	13	6.7	7	34.05	2
240501300800210	13	6.7	8	37.95	2
240501600100210	16	10	1	17.86	2
240501600200210	16	10	2	23.66	2
240501600300210	16	10	3	29.46	2
240501600400210	16	10	4	35.26	2
240501600500210	16	10	5	41.06	2
240501600600210	16	10	6	46.86	2
240501600700210	16	10	7	52.66	2
240501600800210	16	10	8	58.46	2
240502000200210	20	16	2	37.4	2
240502000300210	20	16	3	46.5	2
240502000400210	20	16	4	55.6	2
240502000500210	20	16	5	64.7	2
240502000600210	20	16	6	73.8	2
240502000700210	20	16	7	82.9	2
240502000800210	20	16	8	92	2
240502200200210	22	19	2	55.4	2
240502200300210	22	19	3	66.4	2
240502200400210	22	19	4	77.4	2

240502200500210	22	19	5	88.4	2
240502200600210	22	19	6	99.4	2
240502200700210	22	19	7	110.4	2
240502200800210	22	19	8	121.4	2
240502600200210	26	26.5	2	74.2	2
240502600300210	26	26.5	3	89.5	2
240502600400210	26	26.5	4	104.8	2
240502600500210	26	26.5	5	120.1	2
240502600600210	26	26.5	6	135.4	2
240502600700210	26	26.5	7	150.7	2
240502600800210	26	26.5	8	166	2