



## Chain sling 1-leg with latch hook, grade 10

### Product information

1-Leg chain sling assembly equipped with latch hook and grab hook. Alternative ends are also available, e.g. foundry hooks, shackles etc. Slings are equipped with a load plate.

**Material:** Steel

**Marking:** CE-marked

**Temperature range:** -40 °C up to +200°C

**Finish:** Painted

**Warning:** Not to be heat-treated

**Safety factor:** 4:1

**Grade:** 10

Part code	Chain diameter mm	WLL ton	EWL m	Weight kg	Delivery time
240500600100190	6	1.4	1	2.98	2
240500600200190	6	1.4	2	4.48	2
240500600300190	6	1.4	3	5.98	2
240500600400190	6	1.4	4	7.48	2

240500600500190	6	1.4	5	8.98	2
240500600600190	6	1.4	6	10.48	2
240500600700190	6	1.4	7	11.98	2
240500600800190	6	1.4	8	13.48	2
240500800100190	8	2.5	1	2.98	2
240500800200190	8	2.5	2	4.48	2
240500800300190	8	2.5	3	5.98	2
240500800400190	8	2.5	4	7.48	2
240500800500190	8	2.5	5	8.98	2
240500800600190	8	2.5	6	10.48	2
240500800700190	8	2.5	7	11.98	2
240500800800190	8	2.5	8	13.48	2
240501000100190	10	4	1	5.33	2
240501000200190	10	4	2	7.63	2
240501000300190	10	4	3	9.93	2
240501000400190	10	4	4	12.23	2
240501000500190	10	4	5	14.53	2
240501000600190	10	4	6	16.83	2
240501000700190	10	4	7	19.13	2
240501000800190	10	4	8	21.43	2
240501300100190	13	6.7	1	10.05	2
240501300200190	13	6.7	2	13.95	2
240501300300190	13	6.7	3	17.85	2

240501300400190	13	6.7	4	21.75	2
240501300500190	13	6.7	5	25.65	2
240501300600190	13	6.7	6	29.55	2
240501300700190	13	6.7	7	33.45	2
240501300800190	13	6.7	8	37.35	2
240501600100190	16	10	1	16.16	2
240501600200190	16	10	2	21.96	2
240501600300190	16	10	3	27.76	2
240501600400190	16	10	4	33.56	2
240501600500190	16	10	5	39.36	2
240501600600190	16	10	6	45.16	2
240501600700190	16	10	7	50.96	2
240501600800190	16	10	8	56.76	2
240502000200190	20	16	2	37.4	2
240502000300190	20	16	3	46.5	2
240502000400190	20	16	4	55.6	2
240502000500190	20	16	5	64.7	2
240502000600190	20	16	6	73.8	2
240502000700190	20	16	7	82.9	2
240502000800190	20	16	8	92	2
240502200200190	22	19	2	55.4	2
240502200300190	22	19	3	66.4	2
240502200400190	22	19	4	77.4	2

240502200500190	22	19	5	88.4	2
240502200600190	22	19	6	99.4	2
240502200700190	22	19	7	110.4	2
240502200800190	22	19	8	121.4	2
240502600200190	26	26.5	2	74.2	2
240502600300190	26	26.5	3	89.5	2
240502600400190	26	26.5	4	104.8	2
240502600500190	26	26.5	5	120.1	2
240502600600190	26	26.5	6	135.4	2
240502600700190	26	26.5	7	150.7	2
240502600800190	26	26.5	8	166	2