

## Chain sling 4-leg with latch hook, grade 10

---

### Product information



4-Leg chain sling assembly equipped with latch hooks and grab hooks. Alternative ends are also available, e.g. foundry hooks, shackles etc. Slings are equipped with a load plate.

... [Read more](#)

---

**Material:** Steel

**Marking:** CE-marked

**Temperature range:** -40 °C up to +200°C

**Finish:** Painted

**Warning:** Not to be heat-treated

**Safety factor:** 4:1

**Grade:** 10

## Chain sling 4-leg with latch hook, grade 10

### Technical data

| Part code       | Chain diameter<br>mm | WLL<br>ton | EWL<br>m | Weight<br>kg |
|-----------------|----------------------|------------|----------|--------------|
| 241300600100200 | 6                    | 3          | 1        | 12.52        |
| 241300600200200 | 6                    | 3          | 2        | 18.52        |
| 241300600300200 | 6                    | 3          | 3        | 24.52        |
| 241300600400200 | 6                    | 3          | 4        | 30.52        |
| 241300600500200 | 6                    | 3          | 5        | 36.52        |
| 241300600600200 | 6                    | 3          | 6        | 42.52        |
| 241300600700200 | 6                    | 3          | 7        | 48.52        |
| 241300600800200 | 6                    | 3          | 8        | 54.52        |
| 241300800100200 | 8                    | 5.3        | 1        | 12.52        |
| 241300800200200 | 8                    | 5.3        | 2        | 18.52        |
| 241300800300200 | 8                    | 5.3        | 3        | 24.52        |
| 241300800400200 | 8                    | 5.3        | 4        | 30.52        |
| 241300800500200 | 8                    | 5.3        | 5        | 36.52        |
| 241300800600200 | 8                    | 5.3        | 6        | 42.52        |
| 241300800700200 | 8                    | 5.3        | 7        | 48.52        |
| 241300800800200 | 8                    | 5.3        | 8        | 54.52        |
| 241301000100200 | 10                   | 8.4        | 1        | 22.12        |
| 241301000200200 | 10                   | 8.4        | 2        | 31.32        |
| 241301000300200 | 10                   | 8.4        | 3        | 40.52        |
| 241301000400200 | 10                   | 8.4        | 4        | 49.72        |
| 241301000500200 | 10                   | 8.4        | 5        | 58.92        |
| 241301000600200 | 10                   | 8.4        | 6        | 68.12        |
| 241301000700200 | 10                   | 8.4        | 7        | 77.32        |
| 241301000800200 | 10                   | 8.4        | 8        | 86.52        |
| 241301300200200 | 13                   | 14         | 2        | 56.2         |
| 241301300300200 | 13                   | 14         | 3        | 71.8         |
| 241301300400200 | 13                   | 14         | 4        | 87.4         |
| 241301300500200 | 13                   | 14         | 5        | 103          |
| 241301300600200 | 13                   | 14         | 6        | 118.6        |
| 241301300700200 | 13                   | 14         | 7        | 134.2        |
| 241301300800200 | 13                   | 14         | 8        | 149.8        |

## Chain sling 4-leg with latch hook, grade 10

### Technical data

| Part code       | Chain diameter<br>mm | WLL<br>ton | EWL<br>m | Weight<br>kg |
|-----------------|----------------------|------------|----------|--------------|
| 241301600200200 | 16                   | 21.2       | 2        | 88.04        |
| 241301600300200 | 16                   | 21.2       | 3        | 111.24       |
| 241301600400200 | 16                   | 21.2       | 4        | 134.44       |
| 241301600500200 | 16                   | 21.2       | 5        | 157.64       |
| 241301600600200 | 16                   | 21.2       | 6        | 180.84       |
| 241301600700200 | 16                   | 21.2       | 7        | 204.04       |
| 241301600800200 | 16                   | 21.2       | 8        | 227.24       |
| 241302000200200 | 20                   | 33.6       | 2        | 149.3        |
| 241302000300200 | 20                   | 33.6       | 3        | 185.7        |
| 241302000400200 | 20                   | 33.6       | 4        | 222.1        |
| 241302000500200 | 20                   | 33.6       | 5        | 258.5        |
| 241302000600200 | 20                   | 33.6       | 6        | 294.9        |
| 241302000700200 | 20                   | 33.6       | 7        | 331.3        |
| 241302000800200 | 20                   | 33.6       | 8        | 367.7        |
| 241302200200200 | 22                   | 40         | 2        | 214          |
| 241302200300200 | 22                   | 40         | 3        | 258          |
| 241302200400200 | 22                   | 40         | 4        | 302          |
| 241302200500200 | 22                   | 40         | 5        | 346          |
| 241302200600200 | 22                   | 40         | 6        | 390          |
| 241302200700200 | 22                   | 40         | 7        | 434          |
| 241302200800200 | 22                   | 40         | 8        | 478          |
| 241302600200200 | 26                   | 56         | 2        | 279.4        |
| 241302600300200 | 26                   | 56         | 3        | 340.6        |
| 241302600400200 | 26                   | 56         | 4        | 401.8        |
| 241302600500200 | 26                   | 56         | 5        | 463          |
| 241302600600200 | 26                   | 56         | 6        | 524.2        |
| 241302600700200 | 26                   | 56         | 7        | 585.4        |
| 241302600800200 | 26                   | 56         | 8        | 646.6        |