

Chain sling 4-leg with latch hook, grade 10



Product information

4-Leg chain sling assembly equipped with latch hooks and grab hooks. Alternative ends are also available, e.g. foundry hooks, shackles etc. Slings are equipped with a load plate.

Material: Steel

Marking: CE-marked

Temperature range: -40 °C up to +200°C

Finish: Painted

Warning: Not to be heat-treated

Safety factor: 4:1

Grade: 10

Part code	Chain diameter mm	WLL ton	EWL m	Weight kg	Delivery time
241300600100200	6	3	1	12.52	2
241300600200200	6	3	2	18.52	2
241300600300200	6	3	3	24.52	2
241300600400200	6	3	4	30.52	2

241300600500200	6	3	5	36.52	2
241300600600200	6	3	6	42.52	2
241300600700200	6	3	7	48.52	2
241300600800200	6	3	8	54.52	2
241300800100200	8	5.3	1	12.52	2
241300800200200	8	5.3	2	18.52	2
241300800300200	8	5.3	3	24.52	2
241300800400200	8	5.3	4	30.52	2
241300800500200	8	5.3	5	36.52	2
241300800600200	8	5.3	6	42.52	2
241300800700200	8	5.3	7	48.52	2
241300800800200	8	5.3	8	54.52	2
241301000100200	10	8.4	1	22.12	2
241301000200200	10	8.4	2	31.32	2
241301000300200	10	8.4	3	40.52	2
241301000400200	10	8.4	4	49.72	2
241301000500200	10	8.4	5	58.92	2
241301000600200	10	8.4	6	68.12	2
241301000700200	10	8.4	7	77.32	2
241301000800200	10	8.4	8	86.52	2
241301300200200	13	14	2	56.2	2
241301300300200	13	14	3	71.8	2
241301300400200	13	14	4	87.4	2

241301300500200	13	14	5	103	2
241301300600200	13	14	6	118.6	2
241301300700200	13	14	7	134.2	2
241301300800200	13	14	8	149.8	2
241301600200200	16	21.2	2	88.04	2
241301600300200	16	21.2	3	111.24	2
241301600400200	16	21.2	4	134.44	2
241301600500200	16	21.2	5	157.64	2
241301600600200	16	21.2	6	180.84	2
241301600700200	16	21.2	7	204.04	2
241301600800200	16	21.2	8	227.24	2
241302000200200	20	33.6	2	149.3	2
241302000300200	20	33.6	3	185.7	2
241302000400200	20	33.6	4	222.1	2
241302000500200	20	33.6	5	258.5	2
241302000600200	20	33.6	6	294.9	2
241302000700200	20	33.6	7	331.3	2
241302000800200	20	33.6	8	367.7	2
241302200200200	22	40	2	214	2
241302200300200	22	40	3	258	2
241302200400200	22	40	4	302	2
241302200500200	22	40	5	346	2
241302200600200	22	40	6	390	2

241302200700200	22	40	7	434	2
241302200800200	22	40	8	478	2
241302600200200	26	56	2	279.4	2
241302600300200	26	56	3	340.6	2
241302600400200	26	56	4	401.8	2
241302600500200	26	56	5	463	2
241302600600200	26	56	6	524.2	2
241302600700200	26	56	7	585.4	2
241302600800200	26	56	8	646.6	2