

## Chain sling 2-leg with latch hook, grade 10



### Product information

2-Leg chain sling assembly equipped with latch hooks and grab hooks. Alternative ends are also available, e.g. foundry hooks, shackles etc. Slings are equipped with a load plate.

**Material:** Steel

**Marking:** CE-marked

**Temperature range:** -40 °C up to +200°C

**Finish:** Painted

**Warning:** Not to be heat-treated

**Safety factor:** 4:1

**Grade:** 10

Part code	Chain diameter mm	WLL ton	EWL m	Weight kg	Delivery time
240800600100180	6	2	1	5.86	2
240800600200180	6	2	2	8.86	2
240800600300180	6	2	3	11.86	2
240800600400180	6	2	4	14.86	2

240800600500180	6	2	5	17.86	2
240800600600180	6	2	6	20.86	2
240800600700180	6	2	7	23.86	2
240800600800180	6	2	8	26.86	2
240800800100180	8	3.55	1	5.86	2
240800800200180	8	3.55	2	8.86	2
240800800300180	8	3.55	3	11.86	2
240800800400180	8	3.55	4	14.86	2
240800800500180	8	3.55	5	17.86	2
240800800600180	8	3.55	6	20.86	2
240800800700180	8	3.55	7	23.86	2
240800800800180	8	3.55	8	26.86	2
240801000100180	10	5.6	1	10.76	2
240801000200180	10	5.6	2	15.36	2
240801000300180	10	5.6	3	19.96	2
240801000400180	10	5.6	4	24.56	2
240801000500180	10	5.6	5	29.16	2
240801000600180	10	5.6	6	33.76	2
240801000700180	10	5.6	7	38.36	2
240801000800180	10	5.6	8	42.96	2
240801300100180	13	9.5	1	19.7	2
240801300200180	13	9.5	2	27.5	2
240801300300180	13	9.5	3	35.3	2

240801300400180	13	9.5	4	43.1	2
240801300500180	13	9.5	5	50.9	2
240801300600180	13	9.5	6	58.7	2
240801300700180	13	9.5	7	66.5	2
240801300800180	13	9.5	8	74.3	2
240801600200180	16	14	2	45.12	2
240801600300180	16	14	3	56.72	2
240801600400180	16	14	4	68.32	2
240801600500180	16	14	5	79.92	2
240801600600180	16	14	6	91.52	2
240801600700180	16	14	7	103.12	2
240801600800180	16	14	8	114.72	2
240802000200180	20	22.4	2	70.1	2
240802000300180	20	22.4	3	88.3	2
240802000400180	20	22.4	4	106.5	2
240802000500180	20	22.4	5	124.7	2
240802000600180	20	22.4	6	142.9	2
240802000700180	20	22.4	7	161.1	2
240802000800180	20	22.4	8	179.3	2
240802200200180	22	26.5	2	105.7	2
240802200300180	22	26.5	3	127.7	2
240802200400180	22	26.5	4	149.7	2
240802200500180	22	26.5	5	171.7	2

240802200600180	22	26.5	6	193.7	2
240802200700180	22	26.5	7	215.7	2
240802200800180	22	26.5	8	237.7	2
240802600200180	26	37.5	2	141.4	2
240802600300180	26	37.5	3	172	2
240802600400180	26	37.5	4	202.6	2
240802600500180	26	37.5	5	233.2	2
240802600600180	26	37.5	6	263.8	2
240802600700180	26	37.5	7	294.4	2
240802600800180	26	37.5	8	325	2