

## Tensile Link TL-3.0 Telemetry

---

### Product information



The TL-3.0 is a third-generation Telemetry Tensile Link load cell. A lightweight wireless tension measuring unit that combines a high level of performance with a robust design for harsh environments. With a range up to 800m and a huge battery life of up to 700 hours, the TL-3.0 can be paired with one or a multiple number of TW-3.0-T Telemetry Handheld Displays.

#### Features:

- Light weight aerospace grade aluminium
- Ability to transmit to unlimited handheld displays with up to 12 load cells
- 2.4GHz license free frequency
- High accuracy
- Rebranding option
- 800m signal range
- Remote power on/off feature
- Sleep mode for battery conservation

... [Read more](#)

---

**Marking:** CE-marked, UKCA-marked  
**Temperature range:** -20°C up to +60°C

## Tensile Link TL-3.0 Telemetry

### Technical data

Part code	WLL ton	Weight kg
423500100460	1	1
423500200460	2	1
423500500460	5	2
423501200460	12	2.6
423501700460	17	4
423502500460	25	5
423503500460	35	6.5
423505000460	50	11
423508000460	80	18
423510000460	100	26.5
423512000460	120	29.5
423515000460	150	43.5
423520000460	200	62
423530000460	300	100.5
423540000460	400	200
423550000460	500	220.5