



## Tensile Link TL-3.0 Telemetry

### Product information

The TL-3.0 is a third-generation Telemetry Tensile Link load cell. A lightweight wireless tension measuring unit that combines a high level of performance with a robust design for harsh environments. With a range up to 800m and a huge battery life of up to 700 hours, the TL-3.0 can be paired with one or a multiple number of TW-3.0-T Telemetry Handheld Displays.

#### Features:

- Light weight aerospace grade aluminium
- Ability to transmit to unlimited handheld displays with up to 12 load cells
- 2.4GHz license free frequency
- High accuracy
- Rebranding option
- 800m signal range
- Remote power on/off feature
- Sleep mode for battery conservation

**Marking:** CE-marked, UKCA-marked

**Temperature range:** -20°C up to +60°C

<b>Part code</b>	<b>WLL ton</b>	<b>Weight kg</b>	<b>Delivery time</b>
423500100460	1	1	2
423500200460	2	1	2
423500500460	5	2	2
423501200460	12	2.6	2
423501700460	17	4	2
423502500460	25	5	2
423503500460	35	6.5	2
423505000460	50	11	2
423508000460	80	18	2
423510000460	100	26.5	2
423512000460	120	29.5	2
423515000460	150	43.5	2
423520000460	200	62	2
423530000460	300	100.5	2
423540000460	400	200	2
423550000460	500	220.5	2