

IMER Stand hoist capacity 300 kg

ET 300 Standard equipment

- ✓ Single-phase 230V/50Hz or single-phase 110V/50Hz electric motor
- ✓ Hook with block and wedge
- ✓ IP67 plug
- ✓ Frame with 4 aluminium wheels
- ✓ Upper limit safety device
- ✓ Controls on single-phase version: direct with 3-pushbutton 1.5-m pendant control
- ✓ Positioning brake
- ✓ Self-braking motor with brake rectifier

Applications

It ensures maximum reliability and durability. The gearmotor is built with helical-toothed steel gears in oil bath.



ET 300



Gantry for stand hoists

IMER Stand hoist—capacity 500 kg

BS 500 Standard equipment

- ✓ Three-phase 400V/50Hz electric motor
- ✓ Hook with block and wedge
- ✓ IP67 plug
- ✓ Frame with 4 aluminium wheels
- ✓ Upper limit safety device
- ✓ BT 24V control with 3-pushbutton 1.5m or 25-m pendant control
- ✓ Positioning brake
- ✓ Self-braking motor with brake rectifier

Applications

Thanks to its heavy duty structure and powerful motor, it can withstand continuous working stress at the construction site without effort.



		ET 300	BS 500
Maximum capacity	kg	300	500
Av. Full load lifting speed	m/min	19/18	26
Max. working height	m	25	25
Ø steel rope	mm	5	8
Rope length	m	26	26
Motor power rate 230V/50Hz 3 Phase	kW	1.1 -	- 2.2
Motor speed	rpm	1320 (230V)/1325(110V)	1400
Running current	A	12 (230V)/(110V)	5.2
Machine weight	kg	50 pendant control	90
SPL in operator's position	dB(A)	<75	<80
Dimensions w/l/h	mm	330/780/380	340/740/560
Packing dimensions w/l/h	mm	350/820/440	360/760/630



Gantry for hoists