BVZ

LIFTING GEAR UK HIRE | SALES | SERVICE



Kerb Stone Clamp VZ-M-UNI

Fully mechanical operation for use with any wheel loader, excavator or other carriers.

Standard Specifications:

Lifting eye for attaching to crane hook.


Handles for optimal guidance of the clamp.

Automatic release for the fully automatic switch over from "full" to "empty".

Туре	Gripping Range* W mm (in)	Carrying Capacity kg (lbs)	Dead Weight kg (lbs)	Order-Number
VZ-M-UNI •	900 – 1,065 (35½ – 42¼")	300 (660)	21 (45)	5310.0275

See page 5.29 for the Hydraulic Kerb Stone Clamp VZ-H-UNI

Kerb Stone Handles BZ



The plumb line remains completely free through a short intervening.

We recommend, using the kerb stone handles in pairs.

Galvanised finish

Exchangeable rubber grippers

Туре	Gripping Range* W mm (in)	Inside Height E mm (in)	Gripper Length L mm (in)	Carrying Capacity kg (lbs)	Dead Weight kg (lbs)	Order-Number
BZ O	0 - 400	200	150	150	4	5320.0084
	$(0-15^3/4'')$	(73/4")	(6")	(330)	(9)	
Spare Rubbers BZ						4320.0006

Universal Handle BVZ

A large adjustable opening range means the BVZ can be universally used for all gardeningand landscaping-design products.

Exchangeable rubber metal bars as gripping elements.

► Galvanised finish

Pin bolts to adjust the opening width.



Removable handles



Туре	Gripping Range* W mm (in)	Inside Height E mm (in)	Gripper Length L mm (in)	Carrying Capacity kg (lbs)	Dead Weight kg (lbs)	Order-Number
BVZ®	$0 - 550 \\ (0 - 21^3/4")$	210 (8¹/₄")	200 (7³/₄")	200 (440)	12 (26)	5320.0020





Kerb Stone Handle VZ

Especially suitable for handling concrete kerb stones. The one-sided angular supports which are placed on the kerb stone already in place enable an extremely narrow joint.

 □ Grips longitudinally so that it can be used in tightest spaces.

No deflection of the plumb line.

All models are equipped with a lifting eye.

Technical data contained in this catalogue can be modified without prior notike in the interest of progress. No liability accepted for any misprints, mistakes and errors.

The VZ I + II + III has a galvanised finish.

The VZ II and VZ III come complete with rubber grippers, suitable for moving large slabs. The VZ III is also equipped with automatic release.

ТуреФ	Gripping Range* W mm (in)	Inside Height E mm (in)	Gripper Length L mm (in)	Carrying Capacity kg (lbs)	Dead Weight kg (Ibs)	Order-Number
VZ I	500 - 1,045 (193/4 - 411/4")	40 (11/2")	100 (4")	100 (220)	12 (26)	5310.0140
VZ II	700 – 1,000 (27 1/2 – 39")	50 (2")	200 (73/4")	300 (660)	25 (55)	5310.0141
VZ III	1.000 - 1,700 (39 - 67")	60 (21/4")	420 (161/2")	1,000 (2,200)	60 (132)	5310.0142
HVA-VZ II: Adjustable Height Stop for VZ II, on one side only						4310.0846

*Gripping range indicates the minimum and maximum pack measurements of building materials, which can be picked-up with this grab.

• Durable surface protection by galvanizing