WEZ

# **Grab for Angular Concrete Products WEZ**

Specially developped for handling L-stones and similar products.

The lifting eye can be adjusted to the center of gravity of all prevalent products being lifted to let it hang vertically.

#### **Standard Specifications:**

- Lifting eye for attaching to crane hook.
- Highly durable and exchangeable rubber grippers.
- Automatic release for the fully automatic change over from "full" to "empty".
- Leaves no black marks.

Туре	Gripping Range* W mm (in)	Working Load Limit WLL kg (Ibs)	Dead Weight kg (lbs)	Order-Number
WEZ-2 O	50 – 250 (2" – 9¾")	2,000 (4,400)	55 (120)	5310.0347
WEZ-6 O	50 – 300 (2" – 11¾")	6,000 (13,200)	160 (350)	5310.0375



### **Mechanical Boulder Grab FVZ-UNI**

Suitable for handling bolders.

Stones of almost all shapes can be lifted and laid to the exact millimetre.

With chains (by changing the chain-position,

the clamp can be lifted after setting of the stone).

Automatically adjustable gripping range from 0 to a maximum of 950 mm.

With lifting eye for attaching to crane hook.

Туре	Gripping Range* W mm (in)	Working Load Limit WLL kg (lbs)	Dead Weight kg (lbs)	Order-Number
FVZ-UNI	0 - 950 (0 - 37 <sup>1</sup> /2")	1,500 (3,300)	99 (218)	5310.0272



### Manual Boulder Grab H-FVZ-UNI

A manual bolder grab for smaller bolders which can be carried by two men.


Additionally equipped with a ring-eyelet to be hooked onto any kind of lifting device,

regarding the admissible working load limit.

Equipped with a simple and fast gripping range adjustment.

□ Galvanised finish

Туре	Gripping Range* W mm (in)	Working Load Limit WLL kg (lbs)	Dead Weight kg (lbs)	Order-Number
H-FVZ-UNI O	$0-600 \\ (0-23^{1}/2")$	200 (440)	18 (40)	5320.0086



## Flat Grab FZ

FZ for transport of slabs.

Narrow grippers turn standing slabs or erect laying slabs.

No problem to grip even tight standing slabs.

No damage to the surface of the slabs due to gentle handling with rubber grippers.

► High security by enormous transmission of 5:1.

A spring tension prevents from unintentional slipping off the clamp.

Lifting band instead of chain or rope: low dead weight, no squeezing, no hurts.

Suitable for nearly all kinds of material.

Туре	Gripping Range* W mm (in)	Working Load Limit WLL kg (lbs)	Dead Weight kg (lbs)	Order-Number
FZ	$0-60 (0-2^{1/2''})$	800 (1,760)	6 (13)	5310.0278

\*Gripping range indicates the minimum and maximum pack measurements of building materials, which can be picked-up with this grab.

• Durable surface protection by galvanizing